430 Belle Grove Cir

ATTENTION: Use of this certificate dose not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation infermation necessary to ensure compilation with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE	
BUILDING OWNERS NAME FLAGSHIP VENTURES					POLICY NUMBER	
STREET ADDRESS (Including Apt., Unit, Suite and/or Bidg. Number) OR F.O. ROUTE AND BOX NUMBER 430 Belle Grove Circle					COMPANY NAIC NUMBER	
OTHER GESCRIPTION (Let and Block Munistrin, etc.)						
LOT 152 MULBERRY - PHASE SIX						
RICHMOND HILL GA					71324	
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION						
Provide the following from the proper FIRM (See Instructions):						
1. COMMUNITY NUMBER	2. PANEL NUMBER	1. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AQ Zones, use depth)	
130018	0001	8	4/17/84	A	N/A	
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): LENGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: LENGVD (or other FIRM datum—see Section 8, Item 7)						
SECTION C BUILDING ELEVATION INFORMATION						
1. Using the Elevation Certificate Instructions, Indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of If the NGVD (or other FIRM datum—see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of If feet NGVD (or other FIRM datum—see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is If feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes No (See instructions on Page 4) 5. The reference level elevation is based on: actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which						
case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)						
6. The elevation of the lowest grade immediately adjacent to the building is: 1 10.2 feet NGVD (or other FIRM datum-see Section B, Item 7).						
SECTION D COMMUNITY INFORMATION						
1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is:						

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1—A30, AE, AH, A (with BFE), V1—V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide fleedplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features_If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Sent)					
DAVID A. BRUNSON	<u> </u>					
TITLE						
GA.R.L.S. SOUTHEAST GI						
ADDRESS						
P.O. BOX 968 RICHMO						
SIGNATURE SIGNATURE	12-10-97 (912) 756-221					
Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.						
COMMENTS: NONE						
JOB # 97-157 (LOT 152	MULBERRY - PHG)					
· an -w	TH ON PILES.					
SLAT . PAGE	PIERS, OR COLUMNS					
A V ZOMBR ZOMBR TÜT ZO	À À V INES ZONES ZONES TO-					
- Same	REFERENCE					
PERFECTION TO THE PARTY OF THE	BARE LEVEL REFERENCE LEVEL					
	ELEVATION					
with the same wi	mullim was line					
	AASS BASS					
FLOOD ADMICENT	REPUBLICE LEVEL BASE FLOOD					
ELEVATION REPORT OF THE PROPERTY OF THE PROPER						
- W.S.						
	ADJACENT GRADE					
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.						
Elevations for all A Zones should be measured at the top of the reference level floor.						
Elevations for all V Zenes should be measured at the bottom of the lowest horizental structural member.						